

Carbon Monoxide 5 - 150 ppm

Order No. 64 06 080

Measuring Range:	5 to 150 ppm (20 °C, 50% r.h.)	
Measuring Time:	approx. 80 to 300 s	
Rel. Standard deviation:	± 10%	
Ambient Operating Conditions		
Temperature:	0 to 40 °C	
Humidity:	1 to 50 mg/L (corresp. 2 to 98% r.h. at 40 °C)	
Air Pressure:	700 to 1100hPa	
Cross Sensivity		
No influence at 25 ppm CO by		
≤ 1000 ppm butane	≤ 300 ppm hydrogen sulfide	
≤ 1000 ppm propane	≤ 100 ppm sulfur dioxide	
≤ 500 ppm n-octane	≤ 15 ppm nitrogen dioxide	

Chlorine 0.2 - 10 ppm

Order No. 64 06 010

C

Measuring Range:	0.2 to 10 ppm (20 °C, 50% r.h.)	
Measuring Time:	approx. 30 to 400 s	
Rel. Standard deviation:	± 12%	
Ambient Operating Conditions		
Temperature:	0 to 40 °C	
Humidity:	5 to 12 mg/L (corresp. 30 to 70% r.h. at 20 °C)	
Air Pressure:	700 to 1100hPa	
Cross Sensivity		
No influence at 0.5 ppm chlorine by		
	≤ 10 ppm hydrochloric acid	