

# Methanol 20 - 500 ppm

Order No. 64 06 380

<b>Measuring Range:</b>	20 to 500 ppm (20 °C, 50% r.h.)
<b>Measuring Time:</b>	approx. 200 to 600 s
<b>Rel. Standard deviation:</b>	± 19%
<b>Ambient Operating Conditions</b>	
Temperature:	15 to 30 °C
Humidity:	5 to 25 mg/L (corresp. 16 to 82% r.h. at 30 °C)
Air Pressure:	700 to 1100hPa
<b>Cross Sensivity</b>	
Substance	Display of Analyzer indicates
250 ppm i-propanol	approx. 350 ppm
250 ppm ethanol	approx. 380 ppm
100 ppm n-butanol	approx. 75 ppm

# Methylene Chloride 20 - 400 ppm

Order No. 64 06 510

<b>Measuring Range:</b>	20 to 400 ppm (20 °C, 50% r.h.)
<b>Measuring Time:</b>	approx. 180 to 600 s
<b>Rel. Standard deviation:</b>	± 25%
<b>Ambient Operating Conditions</b>	
Temperature:	10 to 40 °C
Humidity:	1 to 30 mg/L (corresp. 2 to 60% r.h. at 40 °C)
Air Pressure:	700 to 1100hPa
<b>Cross Sensivity</b>	
No influence by	≤ 5 ppm HCl
(at 20 ppm CH <sub>2</sub> Cl <sub>2</sub> )	≤ 0,1 ppm Cl <sub>2</sub>
	≤ 1 Vol% CO <sub>2</sub>
It is impossible to measure methylene chloride in the presence of other chlorinated hydrocarbons	