## ACTUVATE:



## ACTUOLR190B Dehumidifier

## 190 Pints/Day | 115V, 6.8A

The ACTOLR190<sup>B</sup> Dehumidifier is a robust dehumidifier with a hot gas valve system designed for better capacity in low temperatures, foldable handle for easy maneuverability to operate, tough wheels for moving up and down stairs and continuous drainage design to ensure the machine can drain in event of pump failure. The dehumidifier is designed for residential and commercial applications in room sizes between 900 – 1,000 square feet and can pump up to 190 pints per day.

Specifications	
Power Supply	115 V / 60 HZ
Power Consumption	745W (80°F, 60%RH)
Dehumidify Capacity	190 pints / day (90°F, 90% RH) @Saturation
	160 pints / day (86°F, 80% RH)
	95 pints / day (80°F, 60% RH)@AHAM
Current	6.8A (80°F, 60% RH)
Noise Level	≤ 55dB(A)
Air Circulation	386 CFM
Refrigerant	R32 / 13.06oz.
Working Temp (°F)	41° - 95°F
Recommended Room Size	900 - 1,000sq.ft. (height = 8.5ft.) 274.32 - 304.8sq.m (height = 2.59m)
Control Type	Digital
Timing Function	1-24 hours
Humidity Setting Range	10% RH - 90% RH
Cord Length	24ft. 7.3m
Hose Length	19.7ft. 6.0m
Wheel	Semi-pneumatic
Housing	Rotomolded polyethylene

## **Product Features**

- Front access panel for convenient repairs
- 24-hour timing function
- Stackable for storage purposes
- Back air outlet allows for connection to air duct
- Hose quick connect feature
- R32 refrigerant for enhanced energy efficiency and lower global warming potential<sup>1</sup>

For Additional Refrigerant Information, please visit 'www.daikin.com/air/daikin\_tech-knowledge/benefits/r-32

Actuvate products are available from the following distributors: